Welspun

COMMERCIAL FLOORING

BIRCH

ASPEN

WILLOW

WEATHERED

SANDALWOOD

HAZEL

CANOPY

LINDEN

Product Barkwood Timber Collection

Product Specifications

Quality	Tufted Carpet Tile
Yarn	100% Solution Dyed Nylon (NY6+™)
Machine Gauge	1/10 Loop Infinity
Pile Type	Multi Level Loop
Pile Height*	4 mm
Tuft Weight *	542 GSM / 16 Oz
Tuft Density*	4800
Total Thickness*	5.5 mm
Backing System	Extruded PVC (Welspun Ecolite™)
Size	50X50 cm

Installation Method

MONOLITHIC



BRICK



ASHLAR



CERTIFICATIONS

LEED GOLD USGBC

SINGAPORE GREEN BUILDING PRODUCT SGBC EXCELLENT

IGBC GREEN FACTORY BUILDING PLATINUM

VERIFIED by SCS GLOBAL SERVICES ENVIRONMENTAL PRODUCT DECLARATION BASED ON LCA

CRI GREEN LABEL +PLUS

GreenPro

CERTIFIED SUSTAINABILITY ASSESSMENT SCS GLOBAL SERVICES NSF/ANSI 140 CARPET GOLD

ZERO WASTE 98% Waste Diversion Achieved. CERTIFIED by SCS Global Services

CE

OEKO-TEX® CONFIDENCE IN TEXTILES STANDARD 100

OEKO-TEX® INSPIRING CONFIDENCE STeP

ISO 14001:2015 CERTIFIED

ISO 9001:2015 CERTIFIED

ISO 45001:2018 CERTIFIED